



Helical bevel Gear Reducers



a **TECO Group** company

VERSIONS





B... SC Flange Mounting



B... FC Foot Mounting



Foot/Flange Mounting

DIFFERENT VERSIONS ARE AVAILABLE WITH HOLLOW OUTPUT SHAFTS AND SINGLE/DOUBLE SOLID OUTPUT SHAFTS.



BA.. 2 STAGES Foot/Flange Mounting



BA.. 3 STAGES Foot/Flange Mounting DIFFERENT VERSIONS ARE AVAILABLE WITH HOLLOW OUTPUT SHAFTS. SINGLE/DOUBLE SOLID OUTPUT SHAFTS ARE ONLY AVAILABLE FOR THE BA70.



a **TECO Group** company

FEATURES



The technological content of B-Series gear reducers allows for an extraordinary performance/lifespan ratio. These highly versatile gear units are successfully used in a vast number of industrial and civil applications. B-Series units offer excellent value for money and output torque/weight ratio, especially considering that they need very limited servicing. The units are available in cast iron (sizes 063 to 163) or aluminium (sizes A42 to A73) casing.



B-PB Fitted for C-face motor input with flexible coupling



IB With input shaft



CB With compact motor

CAST IRON

SIZES: 060-080-100-125-140-150-160

- Casing with feet FC, flange SC and universal UC
- Gearing 3 reduction stages
- Gleason spiral bevel gear pairs with run-in profile, mounted as second reduction stage for a higher resistance
- High-strength casings optimized with FEM analysis and input and output flanges of grey cast-iron G200 to ensure
- Excellent mechanical strength
- · Gears hardened and tempered with shaved or ground profile
- Load capacity calculated and verified according to ISO 6336 and AGMA 2001
- Painted with RAL 5010 blue epoxy-polyester powder
- ATEX versions available 2GD/3GD



BA C-Face Motor Input, quill mount



IBA With input shaft



CBA With compact motor



ALUMINIUM

SIZES: A40-A50-A70

- Universal casing
- Gearing with 2 and 3 reduction stages
- Hypoid bevel gears for size A40 and A50, gleason bevel gear pairs for size A70, all with run-in profile
- Casing in die-cast aluminium alloy
- Excellent mechanical strength while being and particularly lightweight
- · Gears hardened and tempered with shaved or around profile
- · Load capacity calculated and verified according to ISO 6336 and AGMA 2001
- Painted with RAL 5010 blue epoxy-polyester powder
- ATEX version available 3GD

RANGE



		Ø [in]	Output Torque M ₂ [lb]	Ratio	
			Max	Min	Max
	B063	1.375-1.5	135	5.71	157.42
	B083	1,5	191	7.81	144.7
	B103	2	405	8.13	165.25
	B123	2.375	787	7.97	180.40
	B143	2.75	1124	10.84	187.24
	B153	3.25	1798	10.49	165.42
	B163	4	2923	8.89	154.83
			np up to 75 hp with t between 5.71 and 1		4 pole moto

- Nominal torque up to 115,059 in-lb
- Admissible radial loads max 17985 lb

NEW

- Reinforced input flanges for big cast iron motors
- Increased torsional rigidity thanks to the new cast iron inspection cover
- Metal plate for aggressive environments
- Oil-free gearbox to allow the most suitable choice of lubricant for every application requirement

	Viscosity index		
n ₂ (rpm)	Mineral oil	Synthetic oil	
	+32 ÷ +104 [°F]	+14 ÷ +122 [°F]	
> 210	150	150	
210 ÷ 20	150	220	
20 ÷ 5	220	320	
< 5	320	460	



	Ø [in]	Output Torque M ₂ [lb]	Ratio	
	Max	Min	Max	
BA40	0.75	27	7.62	78.17
BA50	1	49	7.91	342.65
BA70	1.375	101	8.36	442.76

- Power from 0.16 hp up to 5 hp with three phase 4 pole motors
- Reduction ratios between 7.62 and 442.76
- Nominal torque up to 3,744 in-lb
- Admissible radial loads max 2248 lb

ACCESSORIES

TORQUE ARM



Available for the sizes: 063 - 083 - 103 - 123 - A40 - A50 - A70

SHRINK DISK



SOLID OUTPUT SHAFT





Single Output Shaft

Double Output Shaft

OTHER ACCESSORIES

Backstop Device Protection Cover kit Reinforced seals on output shaft and viton seals

OUTPUT FLANGE



FA



FB - FC - FD

	FA	FB	FC	FD
B063	•	•	•	-
B083	•	•	•	-
B103	•	•	•	-
B0123	•	•	•	-
B0143	-	•	-	-
B0153	-	•	•	-
B0163	-	•	-	-
BA40	•	•	•	•
BA50	•	•	•	•
BA70	•	•	-	-
• Availab	ole			

MOTOVARIO HEART OF MOTION a TECO Group company





Available for the sizes: 143 - 153 - 163

- Not available

SALES NETWORK









EUROPE











NORTH AMERICA





ASIA





SOUTH AMERICA





AFRICA





Motovario Corporation

1440 Bluegrass Lakes Parkway - 30004 - Alpharetta (GA) USA Tel. 770-752-0911 - www.motovario.com

